

Submittal Data: MSZ-GS09NA-U1

9,000 BTU/H Wall-Mounted Indoor Unit for MXZ and PUMY Heat Pump System

Job Name:	Location:		
Purchaser:	Submitted By:		
Submitted To:	Reference: App	roval:	Construction:
Engineer:	Date:	Application:	



Images provided for reference purposes only

		images provided for reference purposes of		
Rated Capacity:				
Cooling ¹	Btu/h	9,000		
leat at 47°F ²	Btu/h	10,900		
ndoor Unit Specifications:				
Power Supply		208/230V, 1Ph, 60Hz		
MCA	A	1.00		
llower Motor Full Load Amperage	A	0.75		
Blower Motor Output	W	30		
Airflow Rate at Cooling, Dry	CFM	134 - 160 - 222 - 307 - 381		
Airflow Rate at Cooling, Wet	CFM	121 - 144 - 200 - 276 - 343		
Airflow Rate at Heating, Dry	CFM	134 - 160 - 222 - 307 - 390		
Sound Pressure Level (Cooling)	dB(A)	19 - 22 - 30 - 37 - 43		
Sound Pressure Level (Heating)	dB(A)	19 - 22 - 30 - 37 - 43		
Orain Pipe Size	In. (mm)	5/8 (15.88)		
External Finish Color		Munsell 1.0Y 9.2/0.2		
Unit Dimensions	W: In. (mm)	31-7/16 (798)		
	D: In. (mm)	9-1/8 (232)		
	H: In. (mm)	11-5/8 (295)		
Jnit Weight	Lbs. (kg)	23 (10.4)		
Gas Pipe Size O.D. (Flared)	In. (mm)	3/8 (9.52)		
iquid Pipe Size O.D. (Flared)	In. (mm)	1/4 (6.35)		
Moisture Removal	pints/h	0.4		
Model No.	Description: (Optional Controls)			
MELCO-RETAIL-MINI	Building Automated System DDC Inter	Building Automated System DDC Interface		
AR-40MAAU	Wired Wall Mounted Remote Control	Wired Wall Mounted Remote Control		
AR-CT01MAU-SB	Touch Screen Wired Wall Mounted Co	Touch Screen Wired Wall Mounted Control		
PAC-YT53CRAU-J	Basic Wired Wall Mounted Control	Basic Wired Wall Mounted Control		
MF-CA200	Deluxe Thermostat Interface	Deluxe Thermostat Interface		
AAC-334IF-E	System Control Interface	System Control Interface		
/AC-497IF-E	PAR Control Interface	PAR Control Interface		
MHK2	Wireless Wall Mounted Control	Wireless Wall Mounted Control		
Model No.	Description: (Accessories)	Description: (Accessories)		

AHRI Rated Conditions (Rated data is determined at a fixed compressor speed)

¹Cooling (Indoor // Outdoor) 80°F (26.6°C) DB, 67°F (19.4°C) WB // 95°F (35°C) DB, 75°F (23.9°C) WB

²Heating at 47°F (8.3°C) (Indoor // Outdoor) 70°F (21.1°C) DB, 60°F (15.6°C) WB // 47°F (8.3°C) DB, 43°F (6.1°C) WB

For data on specific Indoor units (all ducted, all non-ducted, and both ducted and non-ducted) combinations, see MXZ Technical and Service Manuals.
Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions.

Note

- 1. Mitsubishi Electric Sales Canada Inc. (MESCA) supports the use of only MESCA supplied and approved components and accessories for proper functioning of the unit(s). Use of non MESCA supported components and accessories will affect warranty coverage. MESCA recommends (A) consideration of all applicable design and application parameters and requirements specific to any project.
- 2. Should any person change this document in any manner whatsoever without MESCA's written permission, the document shall be of no force and effect and any change shall be deemed to be a representation and warranty made by that person and not MESCA. That person, and not MESCA, shall assume full responsibility for the consequences of such changes. MESCA assumes no responsibility for any consequences in such cases.



Submittal Data: MSZ-GS09NA-U1







