

Job Name:		Location:	
Schedule Reference:		Submitted By:	
Submitted To:		Reference:	Approval: Construction:
Engineer:		Date:	Application:
 Standard Model Seacoast (-BS) Model		• Snow/Wind Guards - (See separate submittal)	

Specifications:			
Indoor Model		Non-Ducted	Ducted
Power source		3-phase 3-wire 575V ±10% 60 Hz	
Cooling capacity (Nominal)		BTU/h	120,000
		kW	35.2
	(575)	Power input kW	8.62
	(575)	Current input A	9.6
	(Rated)	BTU/h	115,000
	(Rated)	kW	33.7
(575)	Power input kW	10.55	10.64
	Current input A	11.7	11.8
Temp. range of cooling	Indoor	W.B.	59 ~ 75°F (15 ~ 24°C)
	Outdoor	D.B.	23 ~ 115°F (-5 ~ 46°C)
Heating capacity (Nominal)		BTU/h	135,000
		kW	39.6
	(575)	Power input kW	10.84
	(575)	Current input A	12.0
	(Rated)	BTU/h	129,000
	(Rated)	kW	37.8
(575)	Power input kW	10.40	10.25
	Current input A	11.6	11.4
Temp. range of heating	Indoor	D.B.	59 ~ 81°F (15 ~ 27°C)
	Outdoor	W.B.	- 4 ~ 60°F (-20 ~ 15.5°C)
Indoor unit connectable		Total capacity	50 ~ 150% of outdoor unit capacity
Model / Quantity		P04 ~ P96 / 1 ~ 30	
Sound power level (measured in anechoic room)		dB <A> 83.0	
Refrigerant		High pressure in. (mm) 3/4 (19.05) Braze	
piping diameter		Low pressure in. (mm) 1-1/8 (28.58) Braze	
Minimum Circuit Ampacity		A 21	
Maximum Overcurrent Protection		A 30	
Fan	Type x Quantity	Propeller fan x2	
	Airflow rate	cfm	11,300
		m ³ /min	320
		L/s	5,330
	Control, Driving mechanism		Inverter-control , Brushless DC motor
	Motor output	kW 0.92+0.92	
Compressor	External static press.		0 in.WG (0 Pa)
	Type x Quantity	Inverter scroll hermetic compressor x1	
	Starting method	Inverter	
	Motor output	kW 8.2	
	Case heater	kW 0.045	
	Lubricant	MEL32	
External finish		Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL SY 8/1 or similar>	
External dimension H x W x D		in. (mm) 65 x 68-15/16 x 29-3/16 (1650 x 1,750 x 740)	
Protection devices	High Pressure protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter circuit (COMP./FAN)		Over-heat protection, Over-current protection
	Compressor		-
	Fan Motor		-
Refrigerant	Type x original charge	R410A x 26 lbs + 1 oz (11.8 kg)	
	Control	Indoor LEV and BC Controller	
Net weight		lbs (kg) 700 (349)	
Heat Exchanger		Salt-resistant cross fin & copper tube	
HIC circuit (HIC: Heat Inter-Changer)		-	
Defrosting method		Auto-defrost mode (Reversed refrigerant cycle)	
Optional parts		Joint: CMY-Y102SS-G2,CMY-Y102LS-G2,CMY-R160-J1,CMY-R201,202,301,306S-G,CMY-R302,303,304,305S-G1	
		BC controller: CMB-P104,106,108,1012,1016NU-J2	
		Main BC controller: CMB-P108,1012,1016NU-JA2, CMB-P1016NU-KA2	
		Sub BC controller: CMB-P104,108NU-KB2	
Compressor Operating Range		28.4% to 100%	
AHRI Ratings (Ducted / Non-Ducted)	EER	10.30/10.60	
		17.10/14.40	
		COP @ 47F - COP @ 17F 3.50/3.37 - 2.26/2.26	
		SCHE 28.60/23.80	

Notes:

- Nominal Cooling conditions (Test conditions are based on AHRI 1230) Indoor: 80°FDB./67°FWB. (26.7°CDB./19.4°CWB.), Outdoor: 95°FDB. (35°CDB.)
- Nominal Heating conditions (Test conditions are based on AHRI 1230) Indoor: 70°FDB. (21.1°CDB.), Outdoor: 47°FDB./43°FWB. (8.3°CDB./6.1°CWB.)
- External static pressure option is available (0.12 in.WG, 0.24 in.WG, 0.32 in.WG/30 Pa, 60 Pa, 80 Pa).
- All electrical work shall comply with National (CEC) and local codes and regulations.
- Mitsubishi Electric Sales Canada Inc. (MESCA) supports the use of only MESCA supplied and approved components and accessories for proper functioning of the unit(s).
- Mitsubishi Electric Sales Canada Inc. (MESCA) supports the use of only MESCA supplied and approved Snow Guard / Wind Deflectors / Windscreens and accessories for proper functioning of the unit(s).
- Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will affect warranty coverage.
- Should any person change this document in any manner whatsoever without MESCA's written permission, the document shall be of no force and effect and any change shall be deemed to be a representation and warranty made by that person and not MESCA. That person, and not MESCA, shall assume full responsibility for the consequences of such changes.

MESCA assumes no responsibility for any consequences in such cases.

Outdoor Unit Outline and Dimensions:

