

SUBMITTAL DATA: PCA-A36KA7 & PUZ-HA36NHA5

36,000 BTU/H CEILING-SUSPENDED HEAT PUMP SYSTEM

Job Name:	Engineer:
Purchaser:	Application:
Submitted To:	For: ☐ Reference ☐ Approval ☐ Construction
Submitted By:	Location:
System Designation:	Schedule No.:



Indoor Unit: PCA-A36KA7



Outdoor Unit: PUZ-HA36NHA5

UNIT OPTION:

Standard Model.....PUZ-HA36NHA5

ACCESSORIES:

Indoor

- Remote Controller Kit with i-See Sensor (PAR-SA92MW-E)
- Drain Pump (PAC-SH84DM-E)
- External Heater Adaptor (PAC-SE56RA-E)

Controls

- Wireless Controller (MHK1)
- Advanced Wired Controller (PAR-33MAA)
- Simple Wired Controller (PAC-YT53CRAU)
- Thermostat Interface (PAR-US444CN)
- M-NET Adapter (PAC-SF83MA-E)

Outdoor Unit

- Rear Snow Guard (SG-1-RE)
- Side Snow Guard (SG-1-SD)
- Front Wind Deflector (x2 required) (PE-FR-24-36)

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved Snow Guard / Wind Deflectors / Windscreens and accessories for proper functioning of the unit(s). Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will affect warranty coverage.

SPECIFICATIONS:

Rated Conditions (Capacity / Input)*		
Cooling	Btu/h / W	34,000 / 2,810
Heating at 47° F	Btu/h / W	38,000 / 3,270
Heating at 17° F	Btu/h / W	38,000 / 5,720

* Rating Conditions per AHRI Standard:

Cooling | Indoor: 80° F (27° C) DB / 67° F (19° C) WB; Outdoor: 95° F (35° C) DB / 75° F (24° C) WB
 Heating at 47° F | Indoor: 70° F (21° C) DB / 60° F (16° C) WB; Outdoor: 47° F (8° C) DB / 43° F (6° C) WB
 Heating at 17° F | Indoor: 70° F (21° C) DB / 60° F (16° C) WB; Outdoor: 17° F (-8° C) DB / 15° F (-9° C) WB

Capacity Range		
Cooling	Btu/h	18,000 - 36,000
Heating at 47° F	Btu/h	18,000 - 40,000

Operating Range		
Cooling	0° F** to 115° F (-18° C to 46° C) DB	
Heating	-13° F to 70° F (-25° C to 21° C) DB	

** Windscreens required for cooling operation below 23° F (-5° C)

AHRI Efficiency Rating	
EER	12.1
SEER	16.6
HSPF IV / V	10.3 / 8.2
COP at 47° F	3.41
COP at 17° F	1.95

Electrical Power Requirements	208 / 230V, 1-Phase, 60 Hz
-------------------------------	----------------------------

Minimum Circuit Ampacity (MCA) *	Breaker Size	MOCP (Outdoor)
Indoor 2 AMP	Outdoor 25 AMP	30 AMP
		31 AMP

* All electrical work shall comply with National (CEC) and local codes and regulations.

Indoor Unit		
Fan Motor (ECM)	F.L.A.	0.97
Fan Motor Output	W	160
SHF / Moisture Removal		0.73 / 8.2 pt./h
Field Drainpipe Size O.D.	in. (mm)	1-1/32 (26)

Outdoor Unit		
Compressor		DC INVERTER-driven Twin Rotary
Fan Motor (ECM)	F.L.A.	0.4 + 0.4
Fan Motor Power	W	86 + 86

Airflow Rate (Low-M1-M2-Hi)			
Indoor (Cooling)	DRY	CFM	775-850-920-990
	WET		705-775-850-920
Outdoor	DRY		3,530

Sound Pressure Level		
Indoor (Low-M1-M2-Hi)		37-39-41-43
Outdoor	Cooling	52
	Heating	53


External Dimensions		
Indoor (H x W x D)	In.(mm)	9-1/16 x 63 x 26-3/4 (230 x 1,600 x 680)
Outdoor (H x W x D)		53-1/8 x 37-3/8 x 13 + 1-3/16 (1,350 x 950 x 330 + 30)

Net Weight		
Indoor	Lbs.(kg)	79 (36)
Outdoor		265 (120)

External Finish	
Indoor	White Munsel No. 6.4Y 8.9/0.4
Outdoor	Munsel No. 3Y 7.8 / 1.1

Refrigerant	R410A ; 12lbs., 2oz. (5.5kg)
-------------	------------------------------




Refrigerant Piping (Flared)		
Liquid (High Pressure)	In.(mm)	3/8 (9.52)
Gas (Low Pressure)		5/8 (15.88)
Maximum Total Refrigerant Pipe Length	Ft. (m)	245 (75)
Maximum Vertical Separation	Ft. (m)	100 (30)



Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

DIMENSIONS: PUZ-HA36NHA5


Unit: mm (in.)



Example of Notes

- ①...Refrigerant GAS pipe connection (FLARE)/15.88<5/8>
- ②...Refrigerant LIQUID pipe connection (FLARE)/9.52<3/8>
- *1 ...Indication of STOP VALVE connection location.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.



for a greener tomorrow

