

Job Name:

Schedule Reference:

Date:



GENERAL FEATURES

- Dual set point functionality (*1)
- Compact floor-mount
- Two-speed settings
- Controls can be wall-mounted or unit-mounted in a hidden case
- IT Terminal Plug

OPTIONS

- ☐ External Heater Adapter..... PAC-YU25HT

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved accessories for proper functioning of the unit(s). Use of non-MESCA supported accessories will affect warranty coverage.

Note:

Ventilation air to be introduced independent of indoor units.

Please refer to local codes for the required ventilation rates specific to the application.

*1 – All components of the system must be compatible. For more details on system compatibility, please refer to Technical Bulletin 100-151 available on our website.

Notes:

SPECIFICATIONS

Capacity*

Cooling	12,000 Btu/h
Heating	13,500 Btu/h

Power

Power Source 208 / 230V, 1 phase, 60Hz

Power Consumption

Cooling (208/230V)..... 0.055 / 0.067 kW

Heating (208/230V)..... 0.055 / 0.067 kW

Current

Cooling (208/230V)..... 0.27 / 0.30 A

Heating (208/230V)..... 0.27 / 0.30 A

Minimum Circuit Ampacity (MCA *) (208/230V) . . . 0.34 / 0.38 A

Maximum Overcurrent Protection (MOCP) 15 A

***All electrical work shall comply with National (CEC) and local codes and regulations.**

External Finish Acrylic paint (5Y 8/1)

Dimensions

Inches 24-13/16 h x 46-3/32 w x 8-11/16 d

mm 630 h x 1170 w x 220 d

Net Weight56 lb / 25 kg

Fan

Type x Quantity Sirocco fan x 2

Airflow Rate (Low - High) 247 - 317 CFM

Motor Type..... Single phase induction motor

External Static Pressure..... 0" WG

Air Filter Standard

Refrigerant Pipe Dimensions (R410A)

Liquid 1/4" / 6.35 mm flare

Gas 1/2" / 12.7 mm flare

Drainpipe Dimension O.D. 1-3/32" / 27 mm

Sound Level (Low - High) 37 - 41 dB (A)

* Cooling / Heating capacity indicated at the maximum value at operation under the following conditions:

Cooling | Indoor: 80° F (27° C) DB / 67° F (19° C) WB, Outdoor 95° F (35° C) DB

Heating | Indoor: 70° F (21° C) DB, Outdoor 47° F (8° C) DB / 43° F (6° C) WB

Model: PFFY-P12NEMU-E – DIMENSIONS

Unit : mm(in)

