

Job Name:

Schedule Reference:

Date:

**UNIT OPTION**

Standard Model PUHY-EP336TSNU-A-TH

Seacoast (BS) Model PUHY-EP336TSNU-A-TH-BS

Minimum Operating Temperature

Heating (Outdoor): -25°F (-32°C) WB

Below -22°F (-30°C) WB, an auxiliary heating source is highly recommended.

ACCESSORIES

Snow/Wind Guards - (See separate submittal)

Panel Heater - (PAC-PH02EHYU-E) (x3)

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved Snow Guard / Wind Deflectors / Windscreens and accessories for proper functioning of the unit(s). Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will affect warranty coverage.

Model		PUHY-EP336TSNU-A (-BS)	
Indoor Model		Non-Ducted	Ducted
Power source		3-phase 3-wire 208-230 V ±10% 60 Hz	
Cooling capacity *1 (Nominal)	BTU/h	336,000	
		98.5	
	kW	26.34	
		81.2-73.4	
	(208-230)	320,000	
		93.8	
(Rated)	BTU/h	31.40	
		29.39	
	kW	96.8-87.5	
		90.6-81.9	
	(208-230)	378,000	
		110.8	
Heating capacity *2 (Nominal)	BTU/h	30.01	
		92.5-83.7	
	kW	360,000	
		105.5	
	(208-230)	28.07	
		26.99	
Temp. range of cooling	Indoor	59-75°F (15-24°C)	
		23-126°F (-5-52°C)	
	Outdoor	59-81°F (15-27°C)	
		-13-60°F (-25-15.5°C)	
	(208-230)	86.5-78.2	
		83.2-75.2	
Temp. range of heating	Indoor	59-81°F (15-27°C)	
		-13-60°F (-25-15.5°C)	
	Outdoor	59-81°F (15-27°C)	
		-13-60°F (-25-15.5°C)	
	(208-230)	86.5-78.2	
		83.2-75.2	
Indoor unit connectable	Total capacity	50-130% of outdoor unit capacity	
	Model/Quantity	P04-P96/2-50	
Sound power level (measured in anechoic room) *3		83.5/85.0	
Refrigerant	Liquid pipe	3/4 (19.05) Braided	
	Gas pipe	1-5/8 (41.28) Braided	

Set Model

Model		PUHY-EP120TNU-A (-BS)	PUHY-EP120TNU-A (-BS)	PUHY-EP96TNU-A (-BS)
Minimum Circuit Ampacity (*)		A	55-49	44-40
Maximum Overcurrent Protection (*)		A	90-80	70-60
FAN	Type x Quantity	Propeller fan x 2	Propeller fan x 2	Propeller fan x 2
	Airflow rate	cfm	7,750	6,700
		m3/min	220	190
	Control, Driving mechanism		Inverter-control, Brushless DC motor	Inverter-control, Brushless DC motor
	Motor output	kW	0.46+0.46	0.46+0.46
	*4 External static press.	0 in.WG (0 Pa)	0 in.WG (0 Pa)	0 in.WG (0 Pa)
Compressor	Type x Quantity	Inverter scroll hermetic compressor x 1	Inverter scroll hermetic compressor x 1	Inverter scroll hermetic compressor x 1
	Starting method	Inverter	Inverter	Inverter
	Motor output	kW	7.4 x 1	5.4 x 1
	Case heater	kW	-	-
	Lubricant	MEL32	MEL32	MEL32
External finish		Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 3Y 7.8/1.1 or similar>	Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 3Y 7.8/1.1 or similar>	Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 3Y 7.8/1.1 or similar>
External dimension H x W x D		in. 71-5/8 x 48-7/8 x 29-3/16 mm 1,818 x 1,240 x 740	in. 71-5/8 x 48-7/8 x 29-3/16 mm 1,818 x 1,240 x 740	in. 71-5/8 x 48-7/8 x 29-3/16 mm 1,818 x 1,240 x 740
Protection devices	High pressure protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter circuit (COMP./FAN)		Over-current protection	Over-current protection
	Fan motor		-	-
Refrigerant	Type x original charge	R410A x 21 lbs + 9 oz (9.8 kg)	R410A x 21 lbs + 9 oz (9.8 kg)	R410A x 21 lbs + 9 oz (9.8 kg)
	Control	LEV and HIC circuit		
Net weight		lbs (kg) 633 (287)	633 (287)	622 (282)
Heat exchanger		Salt-resistant cross fin & aluminium tube	Salt-resistant cross fin & aluminium tube	Salt-resistant cross fin & aluminium tube
HIC circuit (HIC: Heat Inter-Changer)		Copper pipe, tube-in-tube structure	Copper pipe, tube-in-tube structure	Copper pipe, tube-in-tube structure
Pipe between unit and distributor	Liquid pipe	in. (mm) 1/2 (12.7) Braided	1/2 (12.7) Braided	3/8 (9.52) Braided
	Gas pipe	in. (mm) 1-1/8 (28.58) Braided	1-1/8 (28.58) Braided	7/8 (22.2) Braided
Defrosting method		Auto-defrost mode (Reversed refrigerant cycle)		
Optional parts		Outdoor Twinning kit: CMY-Y300CBK2 Joint: CMY-Y102SS/102LS-G2, CMY-Y202S/302S-G2 Header: CMY-Y104/108/1010C-G		

Notes:


- Cooling conditions (Test conditions are based on AHRI 1230)
Indoor: 80°F DB/67°F WB, (26.7°C DB/19.4°C WB), Outdoor: 95°F DB, (35°C DB)
- Heating conditions (Test conditions are based on AHRI 1230)
Indoor: 70°F DB, (21.1°C DB), Outdoor: 47°F DB/43°F WB, (8.3°C DB/6.1°C WB)
- Cooling mode/Heating mode
- External static pressure option is available (0.12 in.WG, 0.24 in.WG, 0.32 in.WG/30 Pa, 60 Pa, 80 Pa).

Specifications are subject to change without notice.

* All electrical work shall comply with National (CEC) and local codes and regulations.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Module: PUHY-EP336TSNU-A-TH(-BS) - DIMENSIONS



Twinning pipe connection size

Package unit name	PUHY-EP367SNU-A-(BS)	PUHY-EP360TNU-A-(BS)	PUHY-EP384TNU-A-(BS)	PUHY-EP408TNU-A-(BS)	PUHY-EP432TNU-A-(BS)
Outdoor unit 1	PUHY-EP120TNU-A-(BS)	PUHY-EP120TNU-A-(BS)	PUHY-EP144TNU-A-(BS)	PUHY-EP144TNU-A-(BS)	PUHY-EP144TNU-A-(BS)
Component unit name	Outdoor unit 2	PUHY-EP120TNU-A-(BS)	PUHY-EP120TNU-A-(BS)	PUHY-EP144TNU-A-(BS)	PUHY-EP144TNU-A-(BS)
	Outdoor unit 3	PUHY-EP96TNU-A-(BS)	PUHY-EP120TNU-A-(BS)	PUHY-EP120TNU-A-(BS)	PUHY-EP144TNU-A-(BS)
Outdoor Twinning Kit(optional parts)			CMY-Y300CBK2		
Indoor unit-Twinning pipe 2	a		ø19.05(3/4)		
Gas	b		ø41.28(1-5/8)		
Liquid	c		ø19.05(3/4)		
Twinning pipe 1-Twinning pipe 2	d		ø34.93(1-3/8)		

Note 1. Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.

2. Twinning pipes should not be tilted more than 15 degrees from the horizontal plane.

Be sure to see the Installation Manual for details of Twinning pipe installation.

3. The pipe section before the Twinning pipe (section "a" and "b" in the figure) must have at least 500mm(19-11/16) of straight section

(*including the straight pipe that is supplied with the Twinning pipe).

4. Only use the Twinning pipe by Mitsubishi (optional parts).

	Unit model	Liquid e or g or i	Gas f or h or j
Twinning pipe-Outdoor unit	EP96	ø9.52(3/8)	ø22.2(7/8)
	EP120	ø12.7(1/2)	ø28.58(1-1/8)
	EP140	ø12.7(1/2)	ø28.58(1-1/8)
	EP140	ø12.7(1/2)	ø28.58(1-1/8)

Unit: mm (in.)


Specifications are subject to change without notice.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Module: PUHY-EP96_120TNU-A-TH(-BS) - DIMENSIONS

Unit: mm (in.)

Note 1. Please refer to the next page for information regarding necessary spacing around the unit and foundation work.
2. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C (248°F).



Connecting pipe specifications

Model	Refrigerant pipe		Service valve	
	Liquid	Gas	Liquid	Gas
EP96	ø9.52(3/8) Braze	ø22.2(7/8) Braze*1,2	ø12.7(1/2)	ø28.58(1-1/8)
EPI20	ø9.52(3/8) Braze	ø22.2(7/8) Braze*1,2	ø12.7(1/2)	ø28.58(1-1/8)
EPI44	ø12.7(1/2) Braze	ø28.58(1-1/8) Braze	ø12.7(1/2)	ø28.58(1-1/8)

- *1 Connect the refrigerant pipe to the service valve according to the Installation Manual.
- *2 Indicates dimensions and connection specifications in the case the unit is used in combination with other outdoor units.
- *3 Furthest piping length (OU from IU) ≥ 90m
- *4 Furthest piping length (OU from IU) ≥ 40m

NO.	Usage	Specifications
①	For pipes	Front through hole 148(5-7/8) × 84(3-5/16) Knockout hole
②		Bottom through hole 150(5-15/16) × 94(3-3/4) Knockout hole
③		Front through hole ø62.7(2-1/2) or ø34.5(1-3/8) Knockout hole
④		Front through hole ø43.7(1-3/4) or ø22.2(7/8) Knockout hole
⑤		Bottom through hole ø65(2-9/16) Knockout hole
⑥		Bottom through hole ø52(2-1/16) Knockout hole
⑦	For transmission cables	Front through hole ø34(1-3/8) Knockout hole
⑧		Bottom through hole ø34(1-3/8) Knockout hole

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.