

Job Name:

Schedule Reference:

Date:

**UNIT OPTION**

Standard Model PUHY-EP408TSNU-A1

Seacoast (BS) Model PUHY-EP408TSNU-A1-BS

Minimum Operating Temperature
Heating (Outdoor): -25°F (-32°C) WB

Below -22°F (-30°C) WB, an auxiliary heating source is highly recommended.

ACCESSORIES

Snow/Wind Guards - (See separate submittal)

Panel Heater - (PAC-PH02EHYU-E) (x3)

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved Snow Guard / Wind Deflectors / Windscreens and accessories for proper functioning of the unit(s). Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will affect warranty coverage.

Outdoor Model		PUHY-EP408TSNU-A1 (-BS)	
Indoor Model		Non-Ducted	Ducted
Power source		3-phase 3-wire 208-230 V ±10% 60 Hz	
Cooling capacity *1 (Nominal)	BTU/h	408,000	
		kW	
	Power input	kW	
		34.31	
	(208-230) Current input	A	
		105.8-95.6	
	(Rated)	BTU/h	
		390,000	
	Power input	kW	
		41.87	
(208-230)	Current input	A	
		129.1-116.7	
	BTU/h	118.0-106.7	
		kW	
	Power input	41.87	
		38.28	
	(208-230) Current input	A	
		129.1-116.7	
	BTU/h	118.0-106.7	
		kW	
Temp. range of cooling	Indoor	W.B.	
	Outdoor	D.B.	
Heating capacity *2 (Nominal)	BTU/h	59-75°F (15-24°C)	
		23-126°F (-5-52°C)	
(208-230)	Power input	kW	
		37.71	
	Current input	A	
		116.3-105.1	
	(Rated)	BTU/h	
		430,000	
	Power input	kW	
		126.0	
	(208-230) Current input	A	
		108.9-98.5	
Temp. range of heating	Indoor	D.B.	
	Outdoor	W.B.	
Indoor unit connectable	Total capacity	50-130% of outdoor unit capacity	
	Model/Quantity	P04-P96/3-50	
Sound power level (measured in anechoic room) *3		dB <A>	
Refrigerant		in. (mm)	
piping diameter		in. (mm)	

Set Model

Model		PUHY-EP144TNU-A1 (-BS)	PUHY-EP144TNU-A1 (-BS)	PUHY-EP120TNU-A1 (-BS)
Minimum Circuit Ampacity (*)		A	60-60	60-60
Maximum Overcurrent Protection (*)		A	100-100	100-100
FAN	Type x Quantity	Propeller fan x 2		
	Airflow rate	cfm		
		m3/min		
	Control, Driving mechanism	Inverter-control, Brushless DC motor		
	Motor output	kW		
	External static press.	0 in.WG (0 Pa)		
Compressor	Type x Quantity	Inverter scroll hermetic compressor x 1		
	Starting method	Inverter		
	Motor output	kW		
	Case heater	kW		
	Lubricant	MEL32		
External finish		Pre-coated galvanized steel sheet (+powder coating for -BS type)	Pre-coated galvanized steel sheet (+powder coating for -BS type)	Pre-coated galvanized steel sheet (+powder coating for -BS type)
External dimension H x W x D		in.	71-5/8 x 48-7/8 x 29-3/16	71-5/8 x 48-7/8 x 29-3/16
Protection devices		mm	1,818 x 1,240 x 740	1,818 x 1,240 x 740
Refrigerant	High pressure protection	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)		
	Inverter circuit (COMP, FAN)	Over-current protection		
	Fan motor	-		
	Type x original charge	R410A x 23 lbs + 12 oz (10.8 kg)		
Control		LEV and HIC circuit		
Net weight		lbs (kg)	680 (308)	680 (308)
Heat exchanger		Salt-resistant cross fin & aluminium tube		
HIC circuit (HIC: Heat Inter-Changer)		Copper pipe, tube-in-tube structure		
Pipe between unit and distributor	Liquid pipe	in. (mm)	1/2 (12.7) Brazed	1/2 (12.7) Brazed
	Gas pipe	in. (mm)	1-1/8 (28.58) Brazed	1-1/8 (28.58) Brazed
Defrosting method		Auto-defrost mode (Reversed refrigerant cycle)		
Optional parts		Outdoor Twinning kit: CMY-Y300CBK2 Joint: CMY-Y102SS/102LS-G2, CMY-Y202S/302S-G2 Header: CMY-Y104/108/1010C-G		

Notes:


- Cooling conditions (Test conditions are based on AHRI 1230)
Indoor: 80°F DB / 67°F WB, (26.7°C DB / 19.4°C WB), Outdoor: 95°F DB, (35°C DB)
- Heating conditions (Test conditions are based on AHRI 1230)
Indoor: 70°F DB, (21.1°C DB), Outdoor: 47°F DB / 43°F WB, (8.3°C DB / 6.1°C WB)
- Cooling mode/Heating mode
- External static pressure option is available (0.12 in.WG, 0.24 in.WG, 0.32 in.WG/30 Pa, 60 Pa, 80 Pa).

Specifications are subject to change without notice.

* All electrical work shall comply with National (CEC) and local codes and regulations.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Module: PUHY-EP408TSNU-A1(-BS) - DIMENSIONS



Twinning pipe connection size

Package unit name	(E)P336T/YSNU	(E)P360T/YSNU	(E)P384T/YSNU	(E)P408T/YSNU	(E)P432T/YSNU
Outdoor unit 1	(E)P120T/YSNU	(E)P120T/YSNU	(E)P144T/YSNU	(E)P144T/YSNU	(E)P144T/YSNU
Outdoor unit 2	(E)P120T/YSNU	(E)P120T/YSNU	(E)P144T/YSNU	(E)P144T/YSNU	(E)P144T/YSNU
Outdoor unit 3	(E)P120T/YSNU	(E)P120T/YSNU	(E)P144T/YSNU	(E)P144T/YSNU	(E)P144T/YSNU
Outdoor Twinning Kit(optional parts)	CMY-Y300CBK2	CMY-Y300CBK2	CMY-Y300CBK2	CMY-Y300CBK2	CMY-Y300CBK2
Indoor unit					
~Twinning pipe 1	a	φ 19.05(3/4)	φ 19.05(3/4)	φ 19.05(3/4)	φ 19.05(3/4)
~Twinning pipe 2	b	φ 41.28(1-5/8)	φ 41.28(1-5/8)	φ 41.28(1-5/8)	φ 41.28(1-5/8)
~Twinning pipe 1	c	φ 19.05(3/4)	φ 19.05(3/4)	φ 19.05(3/4)	φ 19.05(3/4)
~Twinning pipe 2	d	φ 34.93(1-3/8)	φ 34.93(1-3/8)	φ 34.93(1-3/8)	φ 34.93(1-3/8)
~Twinning pipe 1	e	φ 12.7(1/2)	φ 12.7(1/2)	φ 12.7(1/2)	φ 12.7(1/2)
~Twinning pipe 2	f	φ 28.58(1-1/8)	φ 28.58(1-1/8)	φ 28.58(1-1/8)	φ 28.58(1-1/8)
~Twinning pipe 1	g	φ 12.7(1/2)	φ 12.7(1/2)	φ 12.7(1/2)	φ 12.7(1/2)
~Twinning pipe 2	h	φ 28.58(1-1/8)	φ 28.58(1-1/8)	φ 28.58(1-1/8)	φ 28.58(1-1/8)
~Twinning pipe 1	i	φ 9.52(3/8)	φ 12.7(1/2)	φ 12.7(1/2)	φ 12.7(1/2)
~Twinning pipe 2	j	φ 22.2(7/8)	φ 28.58(1-1/8)	φ 28.58(1-1/8)	φ 28.58(1-1/8)

Note 1. Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.

2. Twinning pipes must be installed horizontally using a level vessel.

3. Be sure to see the Installation Manual for details of Twinning pipe installation.

4. The pipe section before the Twinning pipe (section "a", "b", "c" and "d" in the figure) must have at least 500mm(19-11/16) of straight section (* including the straight pipe that is supplied with the Twinning pipe).

5. Only use the Twinning pipe by Mitsubishi (optional parts).

Unit: mm (in.)

Module: PUHY-EP120_144NU-A1(-BS) - DIMENSIONS


Unit: mm (in.)

Connecting pipe specifications

Model	Diameter		
	Refrigerant pipe *1		Service valve
	Liquid	Gas	
(E)P96	φ52(3/8)	φ22(7/8)	φ12.7(1/2)
(E)P96	φ12.7(1/2)	φ22(7/8)	φ28.5(1-1/8)
(E)P120	φ52(3/8)	φ28.5(1-1/8)	φ12.7(1/2)
(E)P120	φ12.7(1/2)	φ28.5(1-1/8)	φ28.5(1-1/8)
(E)P144	φ12.7(1/2)	φ28.5(1-1/8)	φ12.7(1/2)
(E)P144	φ12.7(1/2)	φ28.5(1-1/8)	φ28.5(1-1/8)

- *1 Connect the refrigerant pipe to the service valve according to the Installation Manual.
- *2 Indicates dimensions and connection specifications in the case the unit is used in combination with other outdoor units.
- *3 Furthest piping length (OU from IU) ≈ 90m (295ft)
- *4 Furthest piping length (OU from IU) ≈ 40m (131ft)

No.	Usage	Specifications
①	For pipes	Front through hole 148(5-7/8) X 84(3-1/5)
②	For pipes	Bottom through hole 150(5-15/16) X 94(3-3/4)
③	For pipes	Front through hole 162(7-1/2) or 164(3-1/8)
④	For pipes	Front through hole 162(7-1/2) or 164(3-1/8)
⑤	For pipes	Bottom through hole 165(2-9/16)
⑥	For pipes	Bottom through hole 165(2-9/16)
⑦	For transmission cables	Front through hole 165(2-9/16)
⑧	For transmission cables	Bottom through hole 165(2-9/16)



Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.