

Job Name:

Schedule Reference:

Date:

**UNIT OPTION**

Standard Model PUHY-P288TSNU-A1

Seacoast (BS) Model PUHY-P288TSNU-A1-BS

Minimum Operating Temperature

Heating (Outdoor): -25°F (-32°C) WB

Below -22°F (-30°C) WB, an auxiliary heating source is highly recommended.

ACCESSORIES

Snow/Wind Guards - (See separate submittal)

Panel Heater - (PAC-PH01EHYU-E) (x1)

Panel Heater - (PAC-PH02EHYU-E) (x2)

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved Snow Guard / Wind Deflectors / Windscreens and accessories for proper functioning of the unit(s). Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will affect warranty coverage.

Outdoor Model		PUHY-P288TSNU-A1 (-BS)	
Indoor Model		Non-Ducted	Ducted
Power source		3-phase 3-wire 208-230 V ±10% 60 Hz	
Cooling capacity *1 (Nominal)	BTU/h	288,000	
		kW	
	Power input	23.21	
		kW	
	(208-230) Current input	71.5-64.7	
		A	
	(Rated)	BTU/h	
		276,000	
	Power input	26.97	
		kW	
Temp. range of cooling	(208-230) Current input	83.1-75.2	
		A	
	(Rated)	80.6-72.9	
		A	
	Temp. range of	Indoor	
		W.B.	
	cooling	59~75°F (15~24°C)	
		Outdoor	
	D.B.	23~126°F (-5~52°C)	
		W.B.	
Heating capacity *2 (Nominal)	BTU/h	323,000	
		kW	
	Power input	25.23	
		kW	
	(208-230) Current input	77.8-70.3	
		A	
	(Rated)	BTU/h	
		308,000	
	Power input	23.40	
		kW	
Temp. range of heating *3	(208-230) Current input	72.1-65.2	
		A	
	(Rated)	71.0-64.2	
		A	
	Temp. range of	Indoor	
		D.B.	
	heating *3	59~81°F (15~27°C)	
		Outdoor	
	W.B.	-13~60°F (-25~15.5°C)	
		Indoor unit	
Indoor unit connectable	Total capacity	50~130% of outdoor unit capacity	
		Model/Quantity	
	P04~P96/2~50	P04~P96/2~50	
		Sound power level (measured in anechoic room) *4	
	dB <A>	82.5/84.0	
		Refrigerant	
	Liquid pipe	3/4 (19.05) Braze	
		in. (mm)	
	Gas pipe	1-3/8 (34.93) Braze	
		in. (mm)	

Set Model

Model			PUHY-P120TNU-A1 (-BS)	PUHY-P96TNU-A1 (-BS)	PUHY-P72TNU-A1 (-BS)
Minimum Circuit Ampacity (*)		A	50-46	40-36	29-26
Maximum Overcurrent Protection (*)		A	80-70	60-50	45-40
FAN	Type x Quantity		Propeller fan x 2	Propeller fan x 2	Propeller fan x 1
	Airflow rate	cfm	7,750	6,700	6,000
		m3/min	220	190	170
	Control, Driving mechanism		Inverter-control, Brushless DC motor	Inverter-control, Brushless DC motor	Inverter-control, Brushless DC motor
	Motor output	kW	0.46+0.46	0.46+0.46	0.92
	*5	External static press.		0 in.WG (0 Pa)	0 in.WG (0 Pa)
Compressor	Type x Quantity		Inverter scroll hermetic compressor x 1	Inverter scroll hermetic compressor x 1	Inverter scroll hermetic compressor x 1
	Starting method		Inverter	Inverter	Inverter
	Motor output	kW	7.7 x 1	5.5 x 1	3.8 x 1
	Case heater	kW	0.045	0.035	0.035
	Lubricant		MEL32	MEL32	MEL32
External finish			Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 3Y 7.8/1.1 or similar>	Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 3Y 7.8/1.1 or similar>	Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 3Y 7.8/1.1 or similar>
External dimension H x W x D		in.	71-5/8 x 48-7/8 x 29-3/16	71-5/8 x 48-7/8 x 29-3/16	71-5/8 x 36-1/4 x 29-3/16
		mm	1,818 x 1,240 x 740	1,818 x 1,240 x 740	1,818 x 920 x 740
Protection devices	High pressure protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter circuit (COMP./FAN)		Over-current protection	Over-current protection	Over-current protection
	Fan motor		-	-	-
Refrigerant	Type x original charge		R410A x 21 lbs + 9 oz (9.8 kg)	R410A x 21 lbs + 9 oz (9.8 kg)	R410A x 14 lbs + 5 oz (6.5 kg)
	Control		LEV and HIC circuit		
Net weight		lbs (kg)	605 (274)	580 (263)	470 (213)
Heat exchanger			Salt-resistant cross fin & copper tube	Salt-resistant cross fin & copper tube	Salt-resistant cross fin & copper tube
HIC circuit (HIC: Heat Inter-Changer)			Copper pipe, tube-in-tube structure	Copper pipe, tube-in-tube structure	Copper pipe, tube-in-tube structure
Pipe between unit and distributor	Liquid pipe	in. (mm)	1/2 (12.7) Brazed	3/8 (9.52) Brazed	3/8 (9.52) Brazed
	Gas pipe	in. (mm)	1-1/8 (28.58) Brazed	7/8 (22.2) Brazed	7/8 (22.2) Brazed
Defrosting method			Auto-defrost mode (Reversed refrigerant cycle)		
Optional parts			Outdoor Twinning kit: CMY-Y300CBK2 Joint: CMY-Y102SS/102LS-G2,CMY-Y202S/302S-G2 Header: CMY-Y104/108/1010C-G		

Notes:


- Nominal cooling conditions (Test conditions are based on AHRI 1230)
Indoor: 80°F DB/67°F WB, (26.7°C DB/19.4°C WB), Outdoor: 95°F DB, (35°C DB)
- Nominal heating conditions (Test conditions are based on AHRI 1230)
Indoor: 70°F DB, (21.1°C DB), Outdoor: 47°F DB/43°F WB, (8.3°C DB/6.1°C WB)
- When applying product below -4°F, consult your design engineer for cold climate application best practices, including the use of a backup source for heating.
- Cooling mode/Heating mode
- External static pressure option is available (0.12 in. WG, 0.24 in. WG, 0.32 in. WG/30 Pa, 60 Pa, 80 Pa).
- Due to continuing improvement, above specifications may be subject to change without notice.

Specifications are subject to change without notice.

* All electrical work shall comply with National (CEC) and local codes and regulations. Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Module: PUHY-P288TSNU-A1(-BS) - DIMENSIONS

Unit: mm (in.)



Twinning pipe connection size

Package unit name	(E)P264T/YSNU	(E)P288T/YSNU	(E)P312T/YSNU
Outdoor unit 1	(E)P96T/YSNU	(E)P120T/YSNU	(E)P120T/YSNU
Outdoor unit 2	(E)P96T/YSNU	(E)P120T/YSNU	(E)P120T/YSNU
Outdoor unit 3	(E)P72T/YSNU	(E)P72T/YSNU	(E)P72T/YSNU
Outdoor Twinning Kit(optional parts)	CMY-Y300CBK2	CMY-Y300CBK2	CMY-Y300CBK2
Indoor unit			
~Twinning pipe 1	a	φ 19.05(3/4)	φ 19.05(3/4)
~Twinning pipe 2	b	φ 34.93(1-3/8)	φ 34.93(1-3/8)
~Twinning pipe 1	c	φ 19.05(3/4)	φ 19.05(3/4)
~Twinning pipe 2	d	φ 34.93(1-3/8)	φ 34.93(1-3/8)
~Twinning pipe 1	e	φ 9.52(3/8)	φ 12.7(1/2)
~Outdoor unit 1	f	φ 22.2(7/8)	φ 28.58(1-1/8)
~Twinning pipe 2	g	φ 9.52(3/8)	φ 9.52(3/8)
~Outdoor unit 2	h	φ 22.2(7/8)	φ 28.58(1-1/8)
~Twinning pipe 2	i	φ 9.52(3/8)	φ 9.52(3/8)
~Outdoor unit 3	j	φ 22.2(7/8)	φ 22.2(7/8)

Note 1. Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.

2. Twinning pipes must be installed horizontally using a level vessel.

Be sure to see the Installation Manual for details of Twinning pipe installation.

3. The pipe section before the "twinning pipe" (section "a", "b", "c" and "d" in the figure) must have at least 500mm(19-11/16) of straight section

(* including the straight pipe that is supplied with the Twinning pipe).

4. Only use the Twinning pipe by Mitsubishi (optional parts).


Module: PUHY-P72TNU-A1(-BS) - DIMENSIONS

Connecting pipe specifications			
Model	Diameter		
	Refrigerant pipe *1		Service valve
	Liquid	Gas	Liquid Gas
(E)P72	φ 9.52(3/8)	Brazed φ 22.7(7/8)	Brazed φ 9.52(3/8) φ 22.7(7/8)

***1** Connect the refrigerant pipe to the service valve according to the Installation Manual.

No.	Usage	Specifications
①	For pipes	Front through hole 148(5-7/8) X 84(3-1/16) Knockout hole
②		Bottom through hole 150(5-15/16) X 94(3-3/4) Knockout hole
③		Front through hole 62.7(2-1/2) or ϕ 34.5(1-3/8) Knockout hole
④	For wires	Front through hole 47(1-3/4) or ϕ 22.7(1-1/8) Knockout hole
⑤		Bottom through hole 65(2-9/16) Knockout hole
⑥		Bottom through hole 52(2-1/16) Knockout hole
⑦	For transition cables	Front through hole 434(1-3/8) Knockout hole
⑧		Bottom through hole 431(1-3/8) Knockout hole

Unit: mm (in.)



Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Module: PUHY-P96_120TNU-A1(-BS) - DIMENSIONS


Unit: mm (in.)

Connecting pipe specifications

Model	Diameter			
	Refrigerant pipe *1		Service valve	
	Liquid	Gas	Liquid	Gas
(E)P96	φ 9.52(3/8)	φ 22.2(7/8)	Brazed	φ 28.58(1-1/8)
(E)P96	φ 12.7(1/2)	φ 22.2(7/8)	Brazed	φ 28.58(1-1/8)
(E)P120	φ 9.52(3/8)	φ 28.58(1-1/8)	Brazed	φ 28.58(1-1/8)
(E)P120	φ 12.7(1/2)	φ 28.58(1-1/8)	Brazed	φ 28.58(1-1/8)
(E)P144	φ 12.7(1/2)	φ 28.58(1-1/8)	Brazed	φ 28.58(1-1/8)

- *1 Connect the refrigerant pipe to the service valve according to the Installation Manual.
- *2 Indicates dimensions and connection specifications in the case the unit is used in combination with other outdoor units.
- *3 Furthest piping length (OU from IU) ≅ 90m (295ft)
- *4 Furthest piping length (OU from IU) ≅ 40m (131ft)

No.	Usage	Specifications
①	For pipes	Front through hole 148(5-7/8) X 84(3-5/16) Knockout hole
②		Bottom through hole 150(5-15/16) X 94(3-3/4) Knockout hole
③		Front through hole 162(7-1/2) or 164(6-5/8) Knockout hole
④	For wires	Front through hole 148(5-7/8) X 84(3-5/16) Knockout hole
⑤		Bottom through hole 165(2-9/16) Knockout hole
⑥		Front through hole 148(5-7/8) X 84(3-5/16) Knockout hole
⑦	For transmission cables	Front through hole 148(5-7/8) X 84(3-5/16) Knockout hole
⑧		Bottom through hole 165(2-9/16) Knockout hole



Note 1. Please refer to (2/2) for information regarding necessary spacing around the unit and foundation work.
2. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C(248°F).

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.