

Job Name:

Schedule Reference:

Date:

OUTDOOR VRF SYSTEM FEATURES

- Single-phase outdoor unit with variable refrigerant flow (VRF) zoning technology
- Inverter-driven (variable speed) compressor
- Total refrigerant piping length of 984' (300 m)
- Connects up to 9 indoor units
- Uses CITY MULTI indoor units and Controls Network
- Low ambient cooling operation down to -40°C available as an option(*5 *6)

UNIT OPTION

- Standard Model.....PUMY-P36NKMU2
- Sea Coast (-BS) Model.....PUMY-P36NKMU2-BS

OPTIONAL PARTS

- Branch Joint (T-Branch) CMY-Y62-G-E
- Header - Four Branch CMY-Y64-G-E
- Header - Eight Branch CMY-Y68-G-E
- Base Heater PAC-SJ20BH-E
- Snow/Wind Guard (x2) CM-S-FR-NKMU
- Snow/Wind Guard Rear SG-1-RE
- Snow/Wind Guard Side SG-1-SD
- Snow/Wind Guard Blocker CM-S-BLK-NKMU

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved Snow Guard / Wind Deflectors / Windscreens and accessories for proper functioning of the unit(s). Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will affect warranty coverage.

Specifications		Model Name
Unit Type		PUMY-P36NKMU2 (-BS)
Nominal Cooling Capacity	Btu/h *1	36,000
Nominal Heating Capacity	Btu/h *2	42,000
Operating Temperature Range	Cooling (Outdoor) *3 *4	23°F ~ 115°F (-5°C ~ +46°C) DB
	Heating (Outdoor)	-13°F ~ +59°F (-25°C ~ +15°C) WB
External Dimensions (H x W x D)	In. / mm	52-11/16 x 41-11/32 x 13 (+1) / 1,338 x 1050 x 330 (+25)
External Finish / Colour		Galvanized sheets (+power coating for -BS type) / Munsell No.3Y 7.8/1.1
Net Weight	Lbs. / kg	267 / 121
Electrical Power Requirements	Voltage, Phase, Hertz	208 / 230V, 1-phase, 60Hz
Minimum Circuit Ampacity (MCA) *	A	29
Maximum Overcurrent Protection	A	44
Piping Diameter (Flared) (In. / mm)	Liquid (High Pressure)	3/8 / 9.52
	Gas (Low Pressure)	5/8 / 15.88
Indoor Unit	Total Capacity	50 to 130% of Outdoor Unit Capacity
	Model / Quantity	P05 to P36 / 1 to 9
Sound Pressure Levels	dB(A) Clg / Htg	49 / 53
Fan		
Type x Quantity (kW)		Propeller Fan x 2 - (0.074 + 0.074)
Airflow Rate	CFM	3,885
Compressor Operating Range	Cooling	29% to 100%
	Heating	24% to 100%
Compressor Type x Quantity		INVERTER-driven Scroll Hermetic x 1
Compressor Motor Output	kW	2.8
Refrigerant		R410A: 10lbs. + 9oz. (4.8kg)
Lubricant		FV50S (2.3 liters)
High-pressure Protection Device		High pressure Switch, High pressure Sensor
Compressor Protection Device		Compressor thermistor, Overcurrent detection
Inverter Circuit Protection Device		Overcurrent detection, Overheat detection (Heat sink thermistor)
AHRI Ratings Ducted / Non-Ducted	EER	12.6 / 15.0
	SEER	18.3 / 22.3
	COP	NA
	HSPF	11.20 / 12.0
Blue Fin Anti-corrosion Protection: Cellulose- and polyurethane-resin coating treatment applied to condenser coil that protects it from air contaminants; ≥1µm thick; Salt Spray/Test Method - no unusual rust development to 960 hours.		

Notes:

- *1. Nominal cooling conditions (subject to ISO 15042)
Indoor: 27°C D.B./19°C W.B. (81°F D.B./66°F W.B.), Outdoor: 35°C D.B. (95°F D.B.)
Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)
- *2. Nominal heating conditions (subject to ISO 15042)
Indoor: 20°C D.B. (68°F D.B.), Outdoor: 7°C D.B./6°C W.B. (45°F D.B./43°F W.B.)
Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)
- *3. 50 to 115°F (10 to 46°C) D.B.: When connecting PKFY-P06NBMU, PKFY-P08NHMU, PFFY-P06/08/12NEMU, and PFFY-P06/08/12NRMU type indoor unit.
- *4. 5 to 115°F (-15 to 46°C) D.B.: When using an optional front wind baffle.
However, this condition does not apply to the indoor units listed in *3.
- *5. For -40°C cooling ONLY operation a low ambient kit is required along with a front wind deflector. Heating operation is not permitted.
- *6. For Low-Ambient Cooling operation, dip switch SW 3 #1 must be switched to the ON position in the indoor unit to disable heating mode.

Specifications are subject to change without notice.

* All electrical work shall comply with National (NEC) and local codes and regulations.

*Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

