

Job Name:

Schedule Reference:

Date:

**UNIT OPTION**

Standard Model PURY-EP192TSNU-A

Seacoast (BS) Model PURY-EP192TSNU-A-BS

Minimum Operating Temperature

Heating (Outdoor): -25°F (-32°C) WB

Below -22°F (-30°C) WB, an auxiliary heating source is highly recommended.

System requires firmware Ver. 26.35 or later.

ACCESSORIES

Snow/Wind Guards - (See separate submittal)

Panel Heater - (PAC-PH02EHYU-E1) (x2)

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved Snow Guard / Wind Deflectors / Windscreens and accessories for proper functioning of the unit(s). Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will affect warranty coverage.

Notes:

1. Nominal cooling conditions (Test conditions are based on AHRI 1230)
Indoor: 80°F D.B./67°F W.B. (26.7°C D.B./19.4°C W.B.), Outdoor: 95°F D.B. (35°C D.B.)
2. Nominal heating conditions (Test conditions are based on AHRI 1230)
Indoor: 70°F D.B. (21.1°C D.B.), Outdoor: 47°F D.B./43°F W.B. (8.3°C D.B./6.1°C W.B.)
3. Cooling mode/Heating mode
4. The sound pressure level measured by the conventional method in JIS for reference purpose.
5. External static pressure option is available (0.12 in. WG, 0.24 in. WG, 0.32 in. WG/30 Pa, 60 Pa, 80 Pa).

Specifications are subject to change without notice.

Outdoor Model				PURY-EP192TSNU-A (-BS)	
Indoor Model				Non-Ducted	Ducted
Power source				3-phase 3-wire 208-230 V ±10% 60 Hz	
Cooling capacity *1 (Nominal)			BTU/h	192,000	
			kW	56.3	
(208-230)		Power input	kW	13.6	
		Current input	A	41.9-37.9	
(Rated)			BTU/h	184,000	
			kW	53.9	
(208-230)		Power input	kW	15.80	15.90
		Current input	A	48.7-44.0	49.0-44.3
Temp. range of cooling		Indoor	W.B.	59~75°F (15~24°C)	
		Outdoor	D.B.	23~126°F (-5~52°C)	
Heating capacity *2 (Nominal)			BTU/h	215,000	
			kW	63	
(208-230)		Power input	kW	16.02	
		Current input	A	49.4-44.6	
(Rated)			BTU/h	204,000	
			kW	59.8	
(208-230)		Power input	kW	14.46	14.75
		Current input	A	44.5-40.3	45.4-41.1
Temp. range of heating		Indoor	D.B.	59~81°F (15~27°C)	
		Outdoor	W.B.	-13~60°F (-25~15.5°C)	
Indoor unit		Total capacity		50~150% of outdoor unit capacity	
connectable		Model/Quantity		P04~P96/1~48	
Sound power level (measured in anechoic room) *3			dB <A>	80.5/82.0	
Refrigerant piping diameter		High pressure	in. (mm)	7/8 (22.2) Brazed	
		Low pressure	in. (mm)	1-1/8 (28.58) Brazed	


Set Model

Model		PURY-EP96TNU-A (-BS)	PURY-EP96TNU-A (-BS)
Minimum Circuit Ampacity (*)		44-40	44-40
Maximum Overcurrent Protection (*)		70-60	70-60
FAN	Type x Quantity	Propeller fan x 2	Propeller fan x 2
	Airflow rate	cfm 7,400	7,400
		m³/min 210	210
	Control, Driving mechanism	Inverter-control, Brushless DC motor	Inverter-control, Brushless DC motor
	Motor output	0.46+0.46	0.46+0.46
	*4 External static press.	0 in. WG (0 Pa)	0 in. WG (0 Pa)
Compressor	Type x Quantity	Inverter scroll hermetic compressor x 1	Inverter scroll hermetic compressor x 1
	Starting method	Inverter	Inverter
	Motor output	5.5	5.5
	Case heater	-	-
	Lubricant	MEL32	MEL32
External finish		Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 5Y 8/1>	Pre-coated galvanized steel sheet (+powder coating for -BS type) <MUNSELL 5Y 8/1>
External dimension H x W x D		in. 71-5/8 x 48-7/8 x 29-3/16 mm 1,818 x 1,240 x 740	in. 71-5/8 x 48-7/8 x 29-3/16 mm 1,818 x 1,240 x 740
Protection devices	High pressure protection	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter circuit (COMP./FAN)	Over-current protection	Over-current protection
	Fan motor	-	-
Refrigerant	Type x original charge	R410A x 17 lbs + 10 oz (8.0 kg)	R410A x 17 lbs + 10 oz (8.0 kg)
	Control	Indoor LEV and BC controller	Indoor LEV and BC controller
Net weight		lbs (kg) 613 (278)	613 (278)
Heat exchanger		Salt-resistant cross fin & aluminium tube	Salt-resistant cross fin & aluminium tube
HIC circuit (HIC: Heat Inter-Change)		-	-
Pipe between unit and distributor	High pressure	in. (mm) 3/4 (19.05) Braze	3/4 (19.05) Braze
	Low pressure	in. (mm) 7/8 (22.2) Braze	7/8 (22.2) Braze
Defrosting method		Auto-defrost mode (Reversed refrigerant cycle)	
Optional parts		Outdoor Twinning kit: CMY-R200NCBK Joint: CMY-Y102SS-G2, CMY-Y102LS-G2, CMY-Y202S-G2, CMY-R160-J1, CMY-R201, 202, 203, 204, 306S-G, CMY-R302, 303, 304, 305S-G1 Main BC controller: CMB-P108, 1012, 1016NU-JA1, CMB-P1016NU-KA1 Sub BC controller: CMB-P104, 108NU-KB1	

* All electrical work shall comply with National (CEC) and local codes and regulations.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Module: PURY-EP192TSNU-A(-BS) - DIMENSIONS



Twinning pipe connection size

Package unit name	PURY-EP192TSNU-A(-BS)	PURY-EP216TSNU-A(-BS)	PURY-EP240TSNU-A(-BS)	PURY-EP264TSNU-A(-BS)	PURY-EP288TSNU-A(-BS)
Component unit name	Outdoor unit 1 PURY-EP08TNU-A(-BS)	Outdoor unit 2 PURY-EP12TNU-A(-BS)	Outdoor unit 1 PURY-EP12TNU-A(-BS)	Outdoor unit 2 PURY-EP12TNU-A(-BS)	Outdoor unit 1 PURY-EP12TNU-A(-BS)
Outdoor Twinning Kit(optional parts)		CMY-R200NCBK	CMY-R200NCBK	CMY-R300NCBK	CMY-R300NCBK
BC controller					
~Twinning pipe					
High pressure	a	ø22.2(7/8)	ø22.2(7/8)	ø22.2(7/8)	ø22.2(7/8)
Low pressure	b	ø28.58(1-1/8)	ø28.58(1-1/8)	ø28.58(1-1/8)	ø28.58(1-1/8)

* When the piping length is 65m(213ft) or longer, use the ø28.58(1-1/8) pipe for the part that exceeds 65m(213ft).

Note 1. Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.

2. Twinning pipes should not be tilted more than 15 degrees from the horizontal plane.

Be sure to see the Installation Manual for details of Twinning pipe installation.

3. The pipe section before the Twinning pipe (section "a" and "b" in the figure) must have at least 500mm(19-11/16) of straight section (*including the straight pipe that is supplied with the Twinning pipe).


4. Only use the Twinning pipe by Mitsubishi (optional parts).

Unit model	High pressure	Low pressure
EP96	c or e ø19.05(3/4)	d or f ø22.2(7/8)
EP120	ø19.05(3/4)	ø28.58(1-1/8)
EP144	ø22.2(7/8)	ø28.58(1-1/8)

Unit: mm (in.)

Unit: mm (in.)

2. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C (248°F).



Connecting pipe specifications		Diameter			
		Model		Service valve	
		High pressure	Low pressure	High pressure	Low pressure
EP96		ø19.05(3/4) Brazed*1	ø27.27(1 1/8) Brazed*1		
EP120				ø28.58(1 1/8)	ø28.58(1 1/8)
EP144			ø28.58(1 1/8) Brazed*1		

*1 Connect the refrigerant pipe to the service valve according to the Installation Manual.

NO.	Usage	Specifications
(1)	For pipes	Front through hole 148(5-7/8) × 84(3-5/16) Knockout hole
(2)		Bottom through hole 150(5-15/16) × 94(3-3/4) Knockout hole
(3)		Front through hole 150(5-15/16) × 94(3-3/4) Knockout hole
(4)	For wires	Front through hole ø62.7(2-1/2) or ø93.4(5-1/8) Knockout hole
(5)		Front through hole ø43.7(1-3/4) or ø22.2(7/8) Knockout hole
(6)		Bottom through hole ø65(2-9/16) Knockout hole
(7)	For transmission cables	Bottom through hole ø52(2-1/16) Knockout hole
(8)		Front through hole ø34(1-3/8) Knockout hole